

Status Report - G4M (United States of America)

Downloaded on: Oct 02, 2026 8:28 AM CET
Published Date : prior to June 2021

1. Overview

- ☐ In Operation
- ☐ Under Construction
- ☐ Described in

Link to PRIS --

☒ **New Concept**

Number of Units --

Year --

Reference Plant

Name of Site --

Link to PRIS --

Net Power Output (MWe) 25

Gross Power Output (MWe) 25

1.1 Introduction

Founded in 2007 as Hyperion Power Generation Inc., Gen4 Energy was formed to develop the Gen4 Module (G4M), first conceived at the Los Alamos National Laboratory (LANL) in New Mexico. Through the commercialization programme at LANL’s Technology Transfer Division, Hyperion Power Generation was awarded the exclusive licence to utilize the intellectual property and develop the module.




Figure 1. Description of G4M reactor

1.2 Development Milestones

1.3 Design organization or vendor company

1.4 Links to designer/vendor website

1.5 Design Description

1.6 Licensing Application Support Documents

1.7 Reactor Unit in PRIS

2. Category Fields

Table 1: ARIS Category Fields

ARIS Category	Value	Units of Examples
Current/Intended Purpose	Commercial – Electric/Non-Electric	e.g. Commercial – Electric/Non-electric, Prototype/FOAK, Demonstration, Experimental

Main Intended Application (once commercial)	Baseload, Dispatchable	e.g. Baseload, Dispatchable, Off-grid/Remote, Mobile/Propulsion, Non- electric (specify)
Reference Location	Inland	e.g. On Coast, Inland, Below- Ground, Floating-Fixed, Marine-Mobile, Submerged- Fixed (Other-specify)
Reference Site Design (reactor units per site)		e.g. Single Unit, Dual Unit, Multiple Unit (# units)
Core Coolant	PbBi	H2O, D2O, He, CO2, Na, Pb, PbBi, Molten Salts, (Other- specify)
Reactor Core Size (1 core)	30 MWth <= Thermal power < 1000 MWth	e.g. Thermal Power < 30 MWth, 30 MWth ≤ Thermal power < 1000 MWth, 1000 MWth ≤ Thermal power ≤ 3000 MWth, Thermal power > 3000 MWth
Reactor Type	LFR	e.g. PWR, BWR, HWR, SCWR, GCR, GFR, SFR, LFR, MSR, ADS
Reactor Size	SMR	e.g. PWR, SMR
Neutron Moderator	None	e.g. H2O, D2O, He, CO2, Na, Pb, PbBi, Molten Salts, (Other- specify)
NSSS Layout	Loop-type	e.g. Loop-type (# loops), Direct-cycle, Semi-integral, Integral, Pool-type
Primary Circulation	Forced	e.g. Forced (# pumps), Natural
Thermodynamic Cycle	Rankine	e.g. Rankine, Brayton, Combined-Cycle (direct/indirect)
Secondary Side Fluid		e.g. H2O, He, CO2, Na, Pb, PbBi, Molten Salts, (Other- specify)
Fuel Form		e.g. Fuel Assembly/Bundle, Coated Sphere, Plate, Prismatic, Contained Liquid, Liquid Fuel/Coolant
Fuel Lattice Shape		e.g. Square, Hexagonal, Triangular, Cylindrical, Spherical, Other, n/a
Rods/Pins per Fuel Assembly/Bundle		e.g. #, n/a

Fuel Material Type	Nitride	e.g. Oxide, Nitride, Carbide, Metal, Molten Salt, (Other-specify)
Design Status	Conceptual Design	e.g. Conceptual, Detailed, Final (with secure suppliers)
Licensing Status		e.g. DCR, GDR, PSAR, FSAR, Design Licensed (in Country), Under Construction (# units), In Operation (# units)
Neutron Spectrum	Fast	e.g. Fast, Thermal

3. Parameter Fields

Table 2: ARIS Parameter Fields

ARIS Parameter	Value	Units of Examples
Plant Infrastructure		
Design Life	10	Years
Lifetime Capacity Factor		%, defined as Lifetime MWe- yrs delivered / (MWe capacity * Design Life), incl. outages
Major Planned Outages		# days every # months (specify purpose, including refuelling)
Operation / Maintenance Human Resources		# Staff in Operation / Maintenance Crew during Normal Operation
Reference Site Design		n Units/Modules
Capacity to Electric Grid	25	MWe (net to grid)
Non-electric Capacity		e.g. MW(th) heat at x °C, m3/day desalinated water, kg/day hydrogen, etc.
In-House Plant Consumption		MWe
Plant Footprint		m2 (rectangular building envelope)
Site Footprint		m2 (fenced area)
Emergency Planning Zone		km (radius)
Releases during Normal Operation		TBq/yr (Noble Gases / Tritium Gas / Liquids)

Load Following Range and Speed		x – 100%, % per minute
Seismic Design (SSE)		g (Safe-Shutdown Earthquake)
NSSS Operating Pressure (primary side)		MPa(abs), i.e. MPa(g)+0.1, at core outlet
NSSS Operating Pressure (secondary side)		MPa(abs), i.e. MPa(g)+0.1, at secondary side outlet
Primary Coolant Inventory (incl. pressurizer)		kg
Nominal Coolant Flow Rate (primary)		kg/s
Nominal Coolant Flow Rate (secondary)		kg/s
Core Inlet Coolant Temperature		°C
Core Outlet Coolant Temperature	500	°C
Available Temperature as Process Heat Source		°C
NSSS Largest Component		e.g. RPV (empty), SG, Core Module (empty/fuelled), etc.
- NSSS Largest Component Length		mm
- NSSS Largest Component Diameter		mm
- NSSS Largest Component Thickness		mm
- NSSS Largest Component Weight		tonne
Reactor Vessel Material		e.g. SS304, SS316, SA508, 800H, Hastelloy N
Steam Generator Design		e.g. Vertical/Horizontal, U-Tube/ Straight/Helical, cross/counter flow
Secondary Coolant Inventory		kg
Pressurizer Design		e.g. separate vessel, integral, steam or gas pressurised, etc.
Pressurizer Volume		m ³ / m ³ (total / liquid)

Containment Type		Dry (single/double), Dry/Wet Well, Inerted, etc.
Containment Volume		m3
Spent Fuel Pool Capacity and Total Volume		Years of full-power operation / m3
Non Electric Application		-
Core Delta Temperature	500	°C
Fuel/Core		
Single Core Thermal Power	70	MW(th)
Refuelling Cycle	120	months or “continuous”
Fuel Material	Uranium nitride	e.g. UO2, MOX, UF4, UCO
Enrichment (avg./max.)	19.75/--	%
Average Neutron Energy		eV
Fuel Cladding Material	HT-9	e.g. Zr-4, SS, TRISO, E-110, none
Number of Fuel “Units”		Specify as Assembly, Bundle, Plate, Sphere, or n/a
Weight of one Fuel Unit		kg
Total Fissile Loading (initial)		kg fissile material (specify isotopic and chemical composition)
% of fuel outside core during normal operation		Applicable to online refuelling and molten salt reactors
Fraction of fresh-fuel fissile material used up at discharge		%
Core Discharge Burnup		MWd/kgHM (heavy metal, eg U, Pu, Th)
Pin Burnup (max.)		MWd/kgHM
Breeding/Conversion Ratio		Fraction of fissile material bred in-situ over one fuel cycle or at equilibrium core
Reprocessing		e.g. None, Batch, Continuous (FP polishing/actinide removal), etc.
Main Reactivity Control	Rod insertion and B4C ball insertion	e.g. Rods, Boron Solution, Fuel Load, Temperature, Flow Rate, Reflectors

Solid Burnable Absorber		e.g. Gd2O3
Core Volume (active)		m3 (used to calculate power density)
Fast Neutron Flux at Core Pressure Boundary		n/(cm²*s)
Max. Fast Neutron Flux		n/(cm²*s)
Core Control Rod Absorber		-
Core Soluble Neutron Absorber		-
Safety Systems		
Number of Safety Trains	Active / Passive	% capacity of each train to fulfil safety function
- reactor shutdown	N/A	- / - / -
- core injection	N/A	- / - / -
- decay heat removal	Passive	- / - / -
- containment isolation and cooling	N/A	- / - / -
- emergency AC supply (e.g. diesels)	N/A	- / - / -
DC Power Capacity (e.g. batteries)		Hours
Events in which Immediate Operator Action is required		e.g. any internal/external initiating events, none
Limiting (shortest) Subsequent Operator Action Time		Hours (that are assumed when following EOPs)
Severe Accident Core Provisions		e.g. no core melt, IMMR, Core Catcher, Core Dump Tank, MCCI
Core Damage Frequency (CDF)		x/reactor-year (based on reference site and location)
Severe Accident Containment Provisions		e.g., H2 ignitors, PARs, filtered venting etc.
Large Release Frequency (LRF)		x/reactor-year (based on reference site and location)
Overall Build Project Costs Estimate or Range (excluding Licensing, based on the Reference Design Site and Location)		

Construction Time (nth of a kind)		Months from first concrete to criticality
Design, Project Mgmt. and Procurement Effort		Person-years (PY) [DP&P]
Construction and Commissioning Effort		PY [C&C]
Material and Equipment Overnight Capital Cost		Million US\$(2015) [M&E], if built in USA
Cost Breakdown	%[C&C]/%[M&E]	
- Site Development before first concrete		(e.g. 25/10) (30/40) (20/25) (20/10) (5/15) (-----) (to add up to 100/100)
- Nuclear Island (NSSS)		
- Conventional Island (Turbine and Cooling)		
- Balance of Plant (BOP)		
- Commissioning and First Fuel Loading		
Factory / On-Site split in [C&C] effort		%/% of total [C&C] effort in PY (e.g., 60/40)
Nuclear System		
System Steam Flow Rate		kg/s
System Steam Pressure		MPa
System Steam Temperature		°C
System Feedwater Flow Rate		kg/s
System Feedwater Temperature		°C
Reactor Core		
Active Core Height		m
Equivalent Core Diameter		m
Average Linear Heat Rate		kW/m
Average Fuel Power Density		kW/kgU
Average Core Power Density		MW/m ³
Outer Diameter Of Fuel Rods		mm

4. Plant Layout, Site Environment and Grid Integration

SUMMARY FOR BOOKLET

--

4.1 Site Requirements during Construction

4.2 Site Considerations during Operation

4.3 Grid Integration

5. Technical NSSS/Power Conversion System Design

SUMMARY FOR BOOKLET

Description of the nuclear systems

The reactor has been designed to deliver 70 MW of power over a ten year lifetime without refuelling. The materials in the core are uranium nitride fuel, HT-9 as the structural material, lead–bismuth eutectic as the coolant, quartz as the radial reflector, and B4C rods and pellets for in-core reactivity control. The reactor is approximately 1.5 m in diameter and 2.5 m in height, in which there are 24 subassemblies containing the fuel pins. The pin assembly is filled with liquid LBE to provide a high conductivity thermal bond between the fuel and cladding. The gap in the fuel pins has been sized to preclude fuel clad mechanical interference throughout the core's lifetime. A plenum is located at one end, which serves as both a fission gas plenum and a repository for the LBE inside the pin as the fuel swells with burnup.

The core coolant is LBE, with a mixed mean exit temperature of 500°C. This temperature limits the cladding temperature, so that maximum cladding creep over the 10 year lifetime of the reactor is less than 1%. During operational shutdown, decay heat is removed from the G4M by two methods. The first method transfers heat from the core by natural circulation of coolants in the primary and secondary loops to the steam generators. The second removes heat by passive vaporization of water from the surface of the secondary containment vessel.

5.1 Primary Circuit

5.2 Reactor Core and Fuel

5.3 Fuel Handling

5.4 Reactor Protection

5.5 Secondary Side

5.6 Containment/Confinement

5.7 Electrical, I&C and Human Interface

5.8 Unique Technical Design Features (if any)

Transportable factory fuelled design

6. Technology Readiness

SUMMARY FOR BOOKLET

--

6.1 Deployed Reactors

6.2 Reactors under Licensing Review

6.3 Reactors in the Design Stage

7. Safety Concepts

SUMMARY FOR BOOKLET

Description of the safety concept There are two independent, safety grade reactivity control systems in the core: a control rod system comprising 18 B4C control rods and a reserve shutdown system consisting of a central cavity into which B4C spheres may be inserted into the core. Both the control rods and the spheres are inserted into dry wells in the core, which are hexagonally shaped thimbles. These thimbles penetrate the reactor vessel and are sealed from the primary coolant. Both systems can independently take the core to long term cold shutdown. The safety concept of the HPM is driven by a set of design criteria that the designers believe are sufficient to ensure protection of the facility and its surroundings. These criteria are a sealed core, operational simplicity, minimal to no in-core movement, mechanical components and separation of power production and conversion operations.

7.1 Safety Philosophy and Implementation

7.2 Transient/Accident Behaviour

8. Fuel and Fuel Cycle

SUMMARY FOR BOOKLET

--

8.1 Fuel Cycle Options

8.2 Resource Use Optimization

8.3 Unique Fuel/Fuel Cycle Design Features

9. Safeguard & Physical Security

SUMMARY FOR BOOKLET

--

9.1 Safeguards

9.2 Security

9.3 Unique Safeguards and/or Security Features

10. Project Delivery & Economics

SUMMARY FOR BOOKLET

Deployment Status Gen4 Energy announced in April 2012 that they would not be pursuing the US Department of Energy's small modular reactor licensing support programme because they concluded that "use of well-known Light Water Reactor (LWR) technology of 45 to 300 MW intended for deployment in the USA had a much higher probability of success given the [Funding Opportunity Announcement's] stated maximum of two awards"

10.1 Project Preparation and Negotiation

10.2 Construction and Commissioning

10.3 Operation and Maintenance